

2003 Amada FO 3015 4kw + LST3015 Pallet Changer, Amada approved used machine,



Stock No: 1811

Model	Amada FO 3015 4kw Laser + LST3015 Pallet Changer Amada approved used machine rebuilt 2018	Standard Equipment	Cooling Cut (HS-WACS) Z-Axis Sensor (HS-98) NC Autofocus NC Gas Control CE Conformity Partition
Year	2003	Oscillator Specification	Fanuc C - 4000E
Traverse Method	X Axis Head Traverse (Flying Optic) Y Axxis Head Traverse (Flying Optic)	Model:	RF Discharge Excited Fast Axial Flow
Axis Traverse Distance	3420 x 1550 x 200mm (Z Axis)	Type:	4000W
Max. Guaranteed Material Thickness	20mm Mild Steel 15mm Stainless (Oxygen Cut) 10mm Stainless (Clean Cut) 8mm Aluminium (A5052)	Rated Output:	CO2:He2:N2=5:40:55 +/-2% each vol
Max. Feed Speed	80m/min(X & Y Axis) 60m/min (Z Axis)	Laser Gas Mixture:	
Laser Cutting Speed	0 / 20m/min	NC Specification	
Positioning Repeatability	+/- 0.005mm	Model:	Fanuc FS - 160i-L
Axis Drive (X, Y & Z)	AC Servo Motor	Display:	9" Colour LCD
Rated Output	4000W	Data Interface:	RS232C
Electric Power Required (Includes Oscillator)	62KVA 400V +/- 10% 50Hz	Chiller Specification	
Air Required	0.97Mpa 1000/600 l/min	Model:	KKW Reidel PC 200.00 or equiv
Machine Length	9625mm	Type:	Air Cooled, Floor Mounted
Machine Width	2500mm	Water Specification:	Demineralized
Machine Height	2218mm (Tower 6120mm)	Power Requirement:	415V 3 Phase + Earth
Machine Weight	12000kg (Tower 6000kg)	Power Consumption:	21.8KVA
		Dimensions:	1470(L) x 905(W) x 1700mm(H)
		Weight:	420Kg
		Dust Collection Specification	
		Model:	Jetpack 78 or equivalent
		Air Requirements:	17.5Nm³/5?6Bar
		Power Supply:	3 Phase AC Supply 415V 50Hz
		Weight:	670Kg
		Dimensions:	1300(W) x 1383(L) x 2560mm(H)

Features and Benefits

Warranty: Parts and labour warranty (UK). Installation and training available.

Availability: Ex stock.

Condition: Available to view in our Warehouse near Sandbach, Cheshire, UK. Jct17 M6.

Price: P.O.A

