

2001 Amada Europe 258



Stock No: 1354

Model	Amada Europe 258, 27 Station Turret with 3 Autoindexing units, with MP250L and PR250UL automation	Hits per Minutes	1mm Pitch: 1000 H.P.M. 25mm Pitch: 400 H.P.M.
Year	2001	Turret Speed Bi-Directional	25 RPM
Frame Construction	Bridge Type	Punching Accuracy	+ / - 0.1mm
Press Capacity	20 tonnes (200kN)	Ram Stroke Length	32mm
Press Type	Single Circuit, Air Cooled Hydraulic	Axis Drives	AC Servo Motor
Axis Traverse Distance	1270 x 1270mm	Turret Drives	AC Servo Motor
Workable Maximum Sheet Size including 1 reposition + turnover	2000 x 1270mm	Electric Power Required	25Kva 400V +/- 10% 50Hz
Max. Material Thickness	6.0mm	Air Pressure Required	5.0 Kg/cm ²
Max. Hole Diameter	27mm diameter	Air Flow	80 L/min
Max. Material		Machine Length	4370mm
Max. Material Weight	120Kg	Machine Width	4090mm
Max. Hole Diameter	88.9mm	Machine Height	2137mm
No. of Stations	27 Stations: 15 x A (Max. Dia. 12.7mm) 6 x B (Max. Dia. 31.7mm) 1 x C (Max. Dia. 50.8mm) 2 x D (Max. Dia. 88.9mm) Auto Indexing: 2 x B (Max Dia 31.7mm) 1 x C (Max. Dia. 50.8mm)	Machine Weight	10500Kgs
Axis Speed X/Y	82 m/min	Standard Equipment	Perimeter Light Beam Safety System Complete Set Of Vibration Damping Pads
		Model Of NC:	Fanuc 18i
		Display:	10.4" LCD
		Data Interface:	RS232C

Features and Benefits

Warranty: Parts and labour warranty in the UK. Installation and training available in the UK.

Availability: Ex stock

Condition: Available to view in our Warehouse near Sandbach, Cheshire, UK. Jct17 M6.

Price: P.O.A

