

2003 Amada Europe 258



Stock No: 1223

| | |
|--|---|
| Model | Amada Europe 258, 27 Station Turret, 3 Autoindexing units with LKI 250M |
| Year | 2003 |
| Frame Construction | Bridge Type |
| Press Capacity | 20 tonnes (200kN) |
| Press Type | Single Circuit, Air Cooled Hydraulic |
| Axis Traverse Distance | 1270 x 2000mm |
| Workable Maximum Sheet Size including 1 reposition turnover | 1270 x 4000mm |
| Max. Material Thickness | 3.2mm (brush table) |
| Max. Hole Diameter Max. Material | 54mm diameter |
| Max. Material Weight | 120Kg |
| Max. Hole Diameter | 88.9mm |
| No. of Stations | 27 Stations: 15 x A (Max. Dia. 12.7mm) 6 x B (Max. Dia. 31.7mm) 1 x C (Max. Dia. 50.8mm) 2 x D (Max. Dia. 88.9mm) Auto Indexing: 2 x B (Max Dia 31.7mm) 1 x C (Max. Dia. 50.8mm) |
| Axis Speed X/Y | 82 m/min |

| | |
|--|--|
| Hits per Minutes | 1mm Pitch: 1000 H.P.M. 25mm Pitch: 400 H.P.M. |
| Turret Speed Bi-Directional | 25 RPM |
| Punching Accuracy | +/- 0.1mm |
| Ram Stroke Length | 32mm |
| Axis Drives | AC Servo Motor |
| Turret Drives | AC Servo Motor |
| Electric Power Required | 30Kva 400V +/- 10% 50Hz |
| Air Pressure Required | 5.0 Kg/cm? |
| Air Flow | 80 L/min |
| Machine Length | 4370mm |
| Machine Width | 4090mm |
| Machine Height | 2137mm |
| Machine Weight | 11000Kgs |
| Standard Equipment | Perimeter Light Beam Safety System Complete Set Of Vibration Damping Pads |
| Model Of NC: | Fanuc 18i |
| Display: | 10.4" LCD |
| Data Interface: | RS232C |

Features and Benefits

Warranty: 6 months parts and labour warranty. Installation and training included.

Availability: Ex stock, Available to view under power.

Condition: Refurbished in our Warehouse near Sandbach, Cheshire, UK. Jct17 M6.

Price: P.O.A

