
John Taylor Engineering Services Ltd (JTES Ltd)
Units 2 - 4 Congleton Trade Centre
Back Lane, Congleton
Cheshire. CW12 4XJ
Tel: 01260 297 700
Mobile: 07760 284145
Fax: 01470 500270
Email: sales@jtes-machinesales.co.uk
Website: www.jtes-machinesales.co.uk

2008 Amada EMK 3510NT with LKI MP250 Load/Unload



Stock No: 1740

Model	Amada EMK 3510NT electric punch, 58 Station Turret with 4 Auto indexing units and P/F (punch and form), and LKI MP250 Loader / Unloader
Year	2008
Frame Construction	Bridge Type
Press Capacity	30 tonnes (196kN)
Press Type	High speed AC servo direct twin drive
Axis Traverse Distance	1270 x 2500mm
Workable Maximum Sheet Size with Auto Positioning	1270 x 5000mm
Max. Material Thickness	4.5mm normal steel
Max. Material Weight	150Kg
Max. Hole Diameter	114.3mm
No. of Stations	**58 Stations:** 24 x A (Max. Dia. mm) 24 x B (Max. Dia. mm) 4 x C (Max. Dia. mm) 2 x D (Max. Dia. mm) **Auto Indexing:** 2 x B (Max Dia mm) 2 x E (Max. Dia. mm)
Axis Speed X / Y	X 100m/min, Y80m/min
Hits per Minute	500 min (5mm stroke, 25.4mm pitch): 780 min (5mm stroke, 1.0mm pitch): 1800 min (1.4mm stroke, 0.5mm pitch)
Turret Speed Bi-Directional	330 RPM
Punching Accuracy	/ - 0.1mm
Positioning Repeatability	/ - 0.07mm
Ram Stroke Length	37mm
Tool Lubrication	Air Blow System
Axis Drives	AC Servo Motor
Electric Power Required	AC200V 3-Phase 5-/60Hz, 27kVA
Air Pressure Required	5.0 Kgf/cm²
Air Flow	
Machine Length	5526mm
Machine Width	5120mm
Machine Height	2318mm
Machine Weight	23 tons
Standard Equipment	Safety Lightguards
Model Of NC: Data Interface:	AMNC Touch Screen Networkable

Features and Benefits

Warranty: Parts and labour warranty in UK. Installation and training available.

© John Taylor Engineering Ltd 2024

Availability: Ex stock. Automation available

Condition:

Price: P.O.A